

# The Premium collection

## VINTAGE 4 V

12 mm 4-V  
AC5 / 33



8001



8002



8003



8004



8005



8006

*By Quality Floors*

The Premium collection

# VINTAGE 4 V

12 mm 4-V

AC5 / 33



8007



8008



8009

*By Quality Floors*

			The Premium collection
Product	Produits	Product	12 MM AC5 V4
collectie	collection	collection	Vintage 4 V
Dikte in mm	Epaisseur avec sous couche en mm	Total thickness in mm	12
Dikte in inch	Epaisseur en inch totale	Total thickness in inch	0,4724
HDF dikte	Epaisseur du panneau en mm	HDF board thickness	12
Lengte in mm	Longueur en mm	Lenght in mm	1257
Lengte in inch	Longueur en inch	Lenght in inch	49,49
Breedte in mm	Largeur en mm	Width in mm	190,5
Breedte in inch	Largeur en inch	Width in inch	7,5
Product particularity	Particularité	Product particularity	—
Gebruiksklasse	Classe d'usage	Class of use	
Slijtklasse	Abrasion	Abrasion class	AC5
Oppervlakte structuur	Structure de surface	Surface structure	decor specific
Click systeem	Système d'emboîtement	Clip system	uniclick
Hdf plaat	Type de support	Type of support	HDF
v groove	Chanfreins	Bevel edges	V4
Garantie	Garantie	Guarantee	lifetime* max 33 years
Logistic	LOGISTIQUE	Logistic	
Aantal planken per doos	Nbre de lames par kit	Number of boards per box	6
Aantal m2 per doos	Surface par kit en m2	Surface area per box in m2	2,395
Gewicht per pak in kg	Poids par kit en kg	Weight per box in kg	14,549
Aantal dozen per pallet	Nombre de kit par palette	Number of boxes per pallet	52
Aantal m2per pallet	Surface par palette en m2	Surface area per pallet in m2	74,71
Gewicht pallet in kg	Poids palette en kg(kitXnbrkit+15)	Weight per pallet in kg	770
Gebruiks klasse	Résistance a l'abrasion	Using class	AC5
Impact weerstand	Résistance aux chocs	Impact resistance	small ball ≥ 12 N · big ball ≥ 750 mm
Krasweerstand	Résistance aux rayures	Scratch resistance	≥ 4000 rpm
Weerstand	Résistance aux taches	Stain resistance	Group 1+2 : grade 5 Group 3: ≥ grade 5
Sigaret weerstand	Résistance a la brulure de cigarette	Burning cigaret resistance	Cfl s2
Weerstand verkleuring	Résistance a la lumière	Light fastness	grey scale ≥ 4 at blue wool grade 7
Warmteweerstand	Coeff de dissipation thermique	Thermal resistance	0,091 (m²K)/W ± 15%
Formaldehyde	Taux de formaldéhyde	Formaldehyde resistance	E1
Size variation	Variation dimensionnelle	Size variation	—

